



WOOD GLUE

Classic

CHARACTERISTICS

- Universal for all types of wood
- Good bonding strength
- Ready-to-use
- Transparent joint

SCOPE OF USE

- Recommended for assembling and repairing all kind of wood elements; heavy wood, light wood, cork carpentry, cardboard and paper.

APPLICATION

Surface preparation:

Surfaces should be leveled, dry, clean of dust and free of substances which may impair adhesion.

Application procedure:

Apply a thin regular layer of Wood Glue Classic on one of the surfaces by brush or roller. For heavy wood, the glue should be applied on both surfaces. Join the two parts within the open time (approximately 15 minutes, depending on the temperature, humidity and type of wood used). Press for 30 minutes, applying a pressure of 2 to 5 kg/cm². Pressing can either be hot or cold with the usual tools and appliances.

Cleaning:

Remove excess glue with a cloth. Once dry, remove excess glue with a wet cloth.

PACKAGING INFORMATION

Packaging Size	Packaging Type	Pieces/ Carton	IDH	Country of Origin
500g	Tin	24	1485236	Tunisia
1kg	Tin	24	1485235	Tunisia
5kg	Bucket	4	1485238	Tunisia



STORAGE & SHELF LIFE

This product should be stored in its original packaging in a cool, dry place, protected from frost, sparks, and flames. Close packaging after use. Keep away from children.

Shelf life: 12 months from manufacturing date.

TECHNICAL DATA	
Property	Value
Raw material	Synthetic resin glue based on polyvinyl acetate
Application temperature [°C]	4 (minimum)
Joint properties	Elastic, tool-friendly, ageing-resistant
Color	White - dries off transparent
Consumption [g/m ²]	150

HEALTH & SAFETY

Irritating to the eyes and skin. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show this container or label.

The above information, in particular recommendations for the handling and use of our products, is based on our professional knowledge and experience. As materials and conditions may vary with each intended application and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for the intended application method and use. Legal liability cannot be accepted on the basis of the contents of this technical data sheet or any verbal advice given unless there is evidence of wilful intent or gross negligence on our part.

This technical data sheet supersedes all previous editions relevant to this product.